

Refrigerated Air Dryer & Heatless Air Dryer



Heatless Air Dryer



+ Heatless Air Dryers are available up to 50 kg/cm²g

Model	Capacity (CFM)	Working Pressure KG/CM ² G
PCHL-10 (Compact)	10	12.3
PCHL-20 (Compact)	20	12.3
PHL-15	15	12.3
PHL-35	35	12.3
PHL-50	50	12.3
PHL-75	75	12.3
PHL-100	100	12.3
PHL-150	150	12.3
PHL-200	200	12.3
PHL-300	300	12.3
PHL-500	500	12.3

Working Conditions

	Ideal	Maximum
Working pressure	: 4 bar to 10 bar	12.5 bar
Inlet Temperature	: 40° C	50° C
Atmospheric dew point	: -40° C	-60° C
Cycle time	: 2 / 4 minutes	
Electrical	: 220V / 50 Hz / Single Phase	

Refrigerated Air Dryer



+ Refrigerated Air Dryers are available up to 50 kg/cm²g

Model	Capacity (CFM)	Working Pressure KG/CM ² G
PREF-12	12	12.3
PREF-20	20	12.3
PREF-40	40	12.3
PREF-60	60	12.3
PREF-80	80	12.3
PREF-100	100	12.3
PREF-125	125	12.3
PREF-150	150	12.3
PREF-200	200	12.3
PREF-250	250	12.3
PREF-300	300	12.3
PREF-400	400	12.3
PREF-500	500	12.3
PREF-600	600	12.3
PREF-750	750	12.3
PREF-1000	1000	12.3

Operating Condition

	Ideal	Maximum
Inlet Temperature	: 45° C	60° C
Ambient Temperature	: 40° C	50° C
Inlet Pressure	: 7 bar g	16 bar g
Pressure Dew Point	: 3° C	



PARAS™
COMPRESSORS
An ISO 9001 : 2008 Company

Other Range of Products

- + Air Compressors
- + Air Receivers
- + Air / Water Cooled After Coolers
- + Moisture Separators
- + Activated Carbon Filters
- + Automatic Drain Valves
- + Oil Removing Filters
- + Micro Filters

L-4104/2, Phase - IV, G.I.D.C, Vatva, Ahmedabad, Gujarat - 382445. (INDIA)
Ph : (O) 25840168, Tele Fax : 25840082 Email : sales@parascompressor.com